

NDAA
COMPLIANT PRODUCT

STAR-LIGHT PLUS
Color in Darkness Technology

H.265
H.264/MJPEG **30fps**



2.1MP

Resolution



Intelligent Video Analytics



Star-Light Plus™



2.8, 4.0mm
Fixed Lens Options



True WDR

5 YEAR

Warranty

Summary

This NDAA-compliant MEGApiX® IP camera includes 2.8mm and 4.0mm fixed lens options and Star-Light Plus™ color in near-total darkness technology for quality video in any lighting conditions, all in an IP66-rated, IK-10 impact resistant ultra low-profile vandal dome housing. All MEGApiX® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 2.1MP/1080p 1/2.8" image sensor at real-time 30fps
- Star-Light Plus™ color in near-total darkness technology
- 2.8mm fixed lens (DWC-MF2Wi28TW, DWC-MPF2Wi28TW)
- 4.0mm fixed lens (DWC-MF2Wi4TW, DWC-MPF2Wi4TW)
- True Wide Dynamic Range (WDR)
- Triple codecs (H.265, H.264, MJPEG) with simultaneous streaming
- 50' Smart IR™ with intelligent camera sync
- Ultra low-profile vandal dome camera
- Smart DNR™ 3D digital noise reduction
- True day/night mechanical IR cut filter
- Programmable privacy zones
- Auto gain control (AGC)
- Auto white balance (AWB)
- Motion detection
- Two-way audio
- Micro SD/SDHC/SDXC class 10 card slot (card not included)
- PoE class 2 and DC12V
- UL listed
- NDAA compliant
- IP66 environmental-rated dust-tight and water-resistant
- IK 10-rated impact-resistant
- 5 year warranty



Accessories (optional)



DWC-VFWMW
Wall mount
bracket




DWC-VFJUNCW
Junction box



DWC-VFCMW
Ceiling mount
bracket

Dimensions

Unit: Inch (mm)



Specifications



IMAGE	
Image sensor	2.1MP/1080p 1/2.8" CMOS
Total pixels	1945 (H) X 1109 (V)
Minimum scene illumination	0.25 lux (color) 0.0 lux (B/W)
Video output	Local video output CVBS 1.0V p-p (75Ω), 16:9 aspect ratio
LENS	
Focal length	2.8mm, F2.0 (DWC-MF2Wi28TW, DWC-MPF2Wi28TW) 4.0mm, F2.6 (DWC-MF2Wi4TW, DWC-MPF2Wi4TW)
Lens type	Fixed lens
HFOV / VFOV	111° / 62° (DWC-MF2Wi28TW, DWC-MPF2Wi28TW) 86° / 46° (DWC-MF2Wi4TW, DWC-MPF2Wi4TW)
IR distance	50ft range
I/O	
Audio in/out and compression	1/1, G.711
Alarm in/out	1/1
OPERATIONAL	
Intelligent Video Analytics	I/A: intrusion, line crossing, counting line, loitering, enter, exit, tamper (DWC-MF2Wi28TW / DWC-MF2Wi4TW) I/A+: object removed, tailgating, direction, stopped, appear, disappear, object left, logical rules (DWC-MPF2Wi28TW / DWC-MPF2Wi4TW)
Shutter mode	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/15 - 1/32000
Slow shutter	1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10
Auto gain control	Auto
Day and night	Auto, day (color), night (B/W)
3D digital noise reduction	Smart DNR™ 3D-DNR
Wide Dynamic Range (WDR)	True WDR, 120dB
Privacy zone	16 programmable privacy masks
Mirror and flip	Yes
Alarm notifications	Email notifications, FTP, alarm output and SD card recording
Memory slot	Micro SD / SDHC / SDXC (card not included)
NETWORK	
LAN	RJ45 (10/100Base-T)
Video compression type	H.265, H.264, MJPEG
Resolution	H.265: 2.1MP/1080p, 720p, VGA, D1, CIF H.264: 2.1MP/1080p, 720p, VGA, D1, CIF MJPEG: 1280x720, 800x600, VGA, 768x432, D1, CIF
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps - 10Mbps, multi-rate for preview and recording
Bitrate control	v
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4, IPv6
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, TTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3 (MIB-2), ONVIF
Security	HTTPS (TLS), IP filtering, 802.1x, digest authentication (ID/PW)
ONVIF conformance	Yes
Web viewer	OS: Windows®, Mac® OS, Linux® Browser: IE®, Google Chrome®, Mozilla Firefox®, Safari® NOTE: Chrome is recommended for IVA configuration
Video management software	DW Spectrum® IPVMS
ENVIRONMENTAL	
Operating temperature	-4°F - 122°F (-20°C - 50°C)
Operating humidity	10-90% (non-condensing)
IP rating	IP66-rated
IK rating	IK10 impact-resistant
Other certifications	UL listed, CE, FCC, RoHS
ELECTRICAL	
Power requirement	DC 12V, PoE (IEEE 802.3af Class 2). (Adapter not included)
Power consumption	DC12V: max 4W, PoE: max 5.5W
MECHANICAL	
Material	Aluminum vandal housing, polycarbonate dome
Dimensions	4.9" x 2.9" (125 x 74.3 mm)
Weight	0.92 lbs (0.42kg)
Warranty	5 year warranty



Built for Users.™

